



AUTOMATIC TRANSMISSION FLUID

PERFORMANCE PLUS[®] Automatic Transmission Fluid is formulated to reduce wear, protect against corrosion, and last longer in vehicles with automatic and power-shift transmissions. It is recommended for domestic and imported transmissions that specify DEXRON[®]III, DEXRON[®]IIE, DEXRON[®], MERCON[®], Ford ESP-M2C138-CJ, Ford ESP-M2C166-H or Type A Suffix A, Allison C-3/C-4, or Caterpillar TO-2 fluids.

The foundation of Performance Plus Oils are Safety-Kleen's hydro-treated, high VI base oils.

For more than 30 years, Safety-Kleen oil products have performed without fail in the most severe operating conditions.

TYPICAL PROPERTIES

PERFORMANCE PLUS [®]	ATF
Specific Gravity 15.6°C (60°F)	0.862
Kinematic Viscosity	
cSt @ 40°C	32.9
cSt @ 100°C	7.0
Viscosity Index	180
Brookfield Viscosity	
cP @ -40°C	17700
Flash Point, °C	204
Pour Point, °C	-51
Color	Red

Note: Values shown above are representative of current production and may vary within modest ranges

Rev. BYM3G

DEXRON[®] is a registered trademark of General Motors Corp. MERCON[®] is a registered trademark of Ford Motor Company.