



HEAVY DUTY DIESEL XHD-7 10W-30

PERFORMANCE PLUS[®] Heavy-Duty Diesel XHD-7 10W-30 Motor Oil is specifically engineered to meet the latest requirements for EGR/EPF engines. Meets or exceeds API Service CJ-4/SM as well as older API categories CI-4 Plus, CI-4 and CH-4. Recommended for naturally aspirated, turbocharged or supercharged diesel, gasoline, or propane engines.

The foundation of Performance Plus Oils are Safety-Kleen's hydro-treated, high VI, Group II base oils. **For more than 30 years, Safety-Kleen oil products have performed without fail in the most severe operating conditions.**

| TYPICAL PROPERTIES | | |
|--------------------------------|-----|-----------|
| PERFORMANCE PLUS [®] | SAE | 10W-30 |
| API Service | | CJ-4 / SM |
| Kinematic Viscosity | | |
| cSt @ 40°C | | 81.8 |
| cSt @ 100°C | | 12.2 |
| Viscosity Index | | 146 |
| CCS Viscosity | | |
| cP @ -25°C | | 6600 |
| Flash Point, °C | | 222 |
| Pour Point, °C | | -33 |
| Specific Gravity 15.6°C (60°F) | | 0.868 |
| Color (ASTM) | | 4.5 |
| TBN | | 9.5 |
| Sulfated Ash, wt% | | 0.98 |

Note: Values shown above are representative of current production and may vary within modest ranges

Rev. BYMHB