



UNIVERSAL TRACTOR FLUID

PERFORMANCE PLUS[®] Universal Tractor Fluid is a premium transmission / differential / hydraulic fluid with superior anti-wear properties recommended for use in powershift / hydrostatic / manual transmissions, differentials, final drives, wet brakes / clutches, power steering, and PTO drives commonly used in farm and construction equipment, off-highway vehicles, and industrial tractors. Some applications include: Power shift transmissions specifying Allison C-3/C-4 or CAT TO-2 fluids; John Deere J20A, J20C; Ford New Holland M2C -41B, -48B, -48C, -86C, -134D; Kubota B6 (UDT); and Vickers 35VQ25.

The foundation of Performance Plus Oils are Safety-Kleen's hydro-treated, high VI base oils.

For more than 30 years, Safety-Kleen oil products have performed without fail in the most severe operating conditions.

TYPICAL PROPERTIES	
PERFORMANCE PLUS [®]	UTF
Specific Gravity 15.6°C (60°F)	0.869
Kinematic Viscosity cSt @ 40°C	58.7
cSt @ 100°C	9.4
Viscosity Index	140
Brookfield Viscosity cP @ -17°C	2600
Flash Point, °C	226
Pour Point, °C	-42
Color	L 3.0

Note: Values shown above are representative of current production and may vary within modest ranges

Rev. BYM62